

DicroLED RGB™ Eco-LED™ series

Architectural highlights in LEDs



Features include:

- 5 Watt high brightness **full colour changing** spotlight
- Can be plugged straight into low voltage MR16 fittings and controlled with the **Remote Control**
- Many different colour changing modes, including - Fade, Flash or Pause on any colour
- Full room effects possible using a **Master Globe connected to Slave Globes** to change in unison
- Energy efficient, up to **90% reduction in energy consumption** compared to incandescent lights
- Units have continuous life span running **50,000 hours plus** for years of continuous use
- **Environmentally friendly**, containing no mercury or sodium
- Solid state electronic light source (Light Emitting Diode) means virtually no maintenance
- Very **easy to install** safe extra low voltage 12 volts
- Low heat radiation and **no UV emissions**
- Moisture and impact resistant



Specifications	
Watts	5W
Power	12V
Output Luminous Flux	80 Lumens m ²
Beam angle	35 degrees

www.ledfx.com.au



LedFX

All dimensions are approximate. The information provided in this brochure is representative of the actual products available at the time of printing. Due to our continuous product development, the designs and specifications depicted are subject to change without notice. Please confirm all particulars with your sales consultant prior to purchase. Each product is covered by a limited warranty. Full terms and conditions are available from your sales consultant. NeonGlo™, LedStar®, DicroLed™, SplashLite®, Luxstar® & EdgeLed™ are covered by one or more of the following patents: 2001100435/2002100441/2002100439 by Cgm Technologies Pty Ltd. © 2004.

9b Lakewood Blvd. Braeside VIC 3195
P: 03 9588 1282 **F:** 03 9588 2088
E: sales@ledfx.com.au