



www.ledfx.com.au



Features include:

- Waterproof LED modules for illuminating Channel lettering and outdoor halo effects
- Available in yellow, red, green, blue, white and RGB
- Energy efficient, up to **90% reduction in energy consumption** compared to neon
- Units have continuous life span running **60,000 hours plus**
- **Environmentally friendly**, containing no mercury or sodium
- Solid state electronic light source (Light Emitting Diodes) means virtually no maintenance
- Very **easy to install** safe extra low 12 volts
- Low heat radiation and **no UV emissions**

Specifications - 3 LED module	
Watts	.25W
LEDs	3
Power	12V
Output Luminous Flux R	32 Lumens m ²
Output Luminous Flux Y	32 Lumens m ²
Output Luminous Flux B	19 Lumens m ²
Output Luminous Flux G	53 Lumens m ²
Output Luminous Flux W	53 Lumens m ²
Beam angle	80 degrees

Specifications - 4 LED module	
Watts	.25W
LEDs	4
Power	12V
Output Luminous Flux R	38 Lumens m ²
Output Luminous Flux Y	38 Lumens m ²
Output Luminous Flux B	25 Lumens m ²
Output Luminous Flux G	68 Lumens m ²
Output Luminous Flux W	75 Lumens m ²
Beam angle	80 degrees



LedFX

9b Lakewood Blvd. Braeside VIC 3195
 P: 03 9588 1282 F: 03 9588 2088
 E: sales@ledfx.com.au

All dimensions are approximate. The information provided in this brochure is representative of the actual products available at the time of printing. Due to our continuous product development, the designs and specifications depicted are subject to change without notice. Please confirm all particulars with your sales consultant prior to purchase. Each product is covered by a limited warranty. Full terms and conditions are available from your sales consultant. NeonGlo™, LedStar®, DicroLed™, SplashLite®, Luxstar® & EdgeLed™ are covered by one or more of the following patents: 200100435/2002100441/2002100439 by Cgm Technologies Pty Ltd. © 2004.